


1. ELECTRIC MOTOR

- Electric motors are 4 poles and have B35 configuration (with feet) as standard.



B35 type



B5 type

Code	Power	Voltage	Flange diameter	Shaft diameter	Frame size	Assembly
AC3V-0.75-1500-B35	0.75 kW	380 V, three phase, 50 Hz, 4 poles	200 mm	19 mm	80	B35
AC3V-1.1-1500-B35	1.1 kW		200 mm	24 mm	90S	
AC3V-1.5-1500-B35	1.5 kW		200 mm	24 mm	90L	
AC3V-2.2-1500-B35	2.2 kW		250 mm	28 mm	100	
AC3V-3-1500-B35	3 kW		250 mm	28 mm	100	
AC3V-4-1500-B35	4 kW		250 mm	28 mm	112	
AC3V-5.5-1500-B35	5.5 kW		300 mm	38 mm	132S	
AC3V-7.5-1500-B35	7.5 kW		300 mm	38 mm	132M	
AC3V-11-1500-B35	11 kW		350 mm	42 mm	160M	
AC3V-15-1500-B35	15 kW		350 mm	42 mm	160L	
AC3V-18.5-1500-B35	18.5 kW		350 mm	48 mm	180M	
AC3V-22-1500-B35	22 kW		350 mm	48 mm	180L	
AC3V-30-1500-B35	30 kW		400 mm	55 mm	200L	
AC3V-37-1500-B35	37 kW		450 mm	60 mm	225S	
AC3V-45-1500-B35	45 kW		450 mm	60 mm	225M	



INDUSTRIAL POWER UNIT SELECTION - Single Phase

Rev. Date: 22.09.2020

Rev. No: 0

Release Date: 22.09.2020

AC1V-0.25-1500-B35	0.25 kW	220 V, mono phase, 50 Hz, 4 poles	160 mm	14 mm	71	
AC1V-0.37-1500-B35	0.37 kW		200 mm	19 mm	80	
AC1V-0.55-1500-B35	0.55 kW		200 mm	19 mm	80	
AC1V-0.75-1500-B35	0.75 kW		200 mm	19 mm	80	
AC1V-1.1-1500-B35	1.1 kW		200 mm	24 mm	90Sa	
AC1V-1.5-1500-B35	1.5 kW		200 mm	24 mm	90L	
AC1V-2.2-1500-B35	2.2 kW		250 mm	28 mm	100	
AC1V-3-1500-B35	3 kW		250 mm	28 mm	100	